



**DOUBLE STOREY 2.4m TIMBER STUD
TIMBER GROUND FLOOR**

CONSTRUCTION DETAILS

- In Accordance with NZS 3603:1999

WALL BRACING DESIGN

- Design the wall bracing system for a "Heavy Cladding" system as defined by NZS 3604:1999

DESIGN ASSUMPTIONS

- Maximum tributary timber floor width: 3 mtrs
- Suspended floor dead load : 0.5 kPa
- Suspended floor live load : 2 kPa
- Maximum snow load : 0.5kPa
- Ultimate ground bearing of 300kPa in accordance with NZS 3604:1999
- Well drained soil conditions in accordance with NZS 3604:1999

NOTE: ALL BUILDING MUST COMPLY WITH NZS 3604: 1999 AND THE NEW ZEALAND BUILDING CODE

Technical Disclaimer : This information is intended solely as a guide for use of Village Stone products. Before using Village Stone product you should ensure that the product is suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose - appropriate expert advice should always be obtained. Village Stone makes no warranty regarding the use of this information with non-Village Stone product.
© Village Stone, New Zealand.



VILLAGE STONE VENEER DETAILS
Option 7: Double Storey 2.4m Stud
Timber ground floor
 scale 1:20

SK7